

姿図




品番	GSP001DWL2 (36度配光)
光源	LED
定格光束	380lm
1/2 照度角	35.8°
ビーム角	35.8°

器具効率 100%	上方光束 0%	下方光束 100%	保守率 100%
-----------	---------	-----------	----------

照明率表

反射率	天井	70%						50%						30%						0%	
		50%		30%		10%		50%		30%		10%		50%		30%		10%		0%	
		30%	10%	30%	10%	30%	10%	30%	10%	30%	10%	30%	10%	30%	10%	30%	10%	30%	10%	0%	
	壁																				
	床																				
	0.6	0.85	0.81	0.80	0.78	0.76	0.75	0.83	0.80	0.79	0.77	0.76	0.75	0.82	0.80	0.78	0.77	0.76	0.75	0.74	
	0.8	0.92	0.87	0.87	0.84	0.83	0.82	0.90	0.86	0.86	0.83	0.83	0.81	0.88	0.85	0.85	0.83	0.82	0.81	0.80	
	1.0	0.97	0.90	0.92	0.88	0.88	0.86	0.94	0.90	0.90	0.87	0.87	0.85	0.92	0.89	0.89	0.87	0.86	0.85	0.84	
	1.25	1.00	0.92	0.95	0.89	0.91	0.87	0.97	0.91	0.93	0.89	0.89	0.87	0.94	0.90	0.91	0.88	0.88	0.86	0.85	
	1.5	1.01	0.93	0.96	0.90	0.92	0.88	0.98	0.92	0.94	0.89	0.91	0.87	0.95	0.90	0.91	0.88	0.89	0.87	0.85	
	2.0	1.06	0.96	1.01	0.93	0.98	0.91	1.02	0.94	0.98	0.92	0.95	0.91	0.98	0.93	0.95	0.91	0.92	0.90	0.88	
	2.5	1.09	0.98	1.05	0.96	1.01	0.94	1.04	0.96	1.01	0.94	0.98	0.93	0.99	0.95	0.97	0.93	0.95	0.92	0.90	
	3.0	1.11	0.99	1.07	0.97	1.04	0.96	1.06	0.97	1.03	0.96	1.00	0.94	1.01	0.96	0.99	0.94	0.97	0.93	0.91	
	4.0	1.16	1.03	1.14	1.02	1.11	1.01	1.10	1.01	1.08	1.00	1.07	0.99	1.05	0.99	1.03	0.99	1.02	0.98	0.96	
	5.0	1.18	1.03	1.15	1.02	1.13	1.01	1.11	1.01	1.09	1.00	1.08	1.00	1.05	0.99	1.04	0.99	1.03	0.98	0.96	
	10.0	1.22	1.06	1.21	1.06	1.20	1.05	1.15	1.04	1.14	1.04	1.13	1.03	1.08	1.02	1.08	1.02	1.07	1.02	0.99	

配光曲線



水平面照度

