

姿図




品番	GSP002DBL2 (36度配光)
光源	LED
定格光束	419lm
1/2 照度角	35.2°
ビーム角	35.2°

器具効率 100%	上方光束 0%	下方光束 100%	保守率 100%
-----------	---------	-----------	----------

照明率表

反射率		70%						50%						30%						0%		
		50%		30%		10%		50%		30%		10%		50%		30%		10%		0%		
		天井	壁	床	天井	壁	床	天井	壁	床	天井	壁	床	天井	壁	床	天井	壁	床	天井	壁	床
0.6	0.86	0.82	0.81	0.79	0.78	0.76	0.85	0.81	0.80	0.78	0.77	0.76	0.83	0.81	0.80	0.78	0.77	0.76	0.75			
0.8	0.93	0.88	0.88	0.85	0.85	0.83	0.91	0.87	0.87	0.85	0.84	0.83	0.90	0.86	0.86	0.84	0.83	0.82	0.81			
1.0	0.98	0.92	0.93	0.89	0.90	0.87	0.96	0.91	0.92	0.88	0.88	0.86	0.94	0.90	0.90	0.88	0.87	0.86	0.85			
1.25	1.01	0.93	0.96	0.91	0.92	0.88	0.98	0.92	0.94	0.90	0.91	0.88	0.95	0.91	0.92	0.89	0.89	0.87	0.86			
1.5	1.03	0.94	0.98	0.91	0.94	0.89	0.99	0.93	0.95	0.90	0.92	0.88	0.96	0.92	0.92	0.89	0.90	0.88	0.86			
2.0	1.07	0.97	1.03	0.95	0.99	0.93	1.03	0.96	0.99	0.93	0.96	0.92	0.99	0.94	0.96	0.92	0.94	0.91	0.89			
2.5	1.10	0.99	1.06	0.97	1.02	0.95	1.05	0.97	1.02	0.95	0.99	0.94	1.01	0.96	0.98	0.94	0.96	0.93	0.91			
3.0	1.13	1.00	1.09	0.98	1.06	0.97	1.07	0.99	1.04	0.97	1.02	0.96	1.02	0.97	1.00	0.96	0.98	0.94	0.92			
4.0	1.18	1.04	1.15	1.03	1.13	1.02	1.12	1.02	1.10	1.01	1.08	1.01	1.06	1.01	1.05	1.00	1.03	0.99	0.97			
5.0	1.19	1.04	1.17	1.03	1.14	1.02	1.12	1.02	1.11	1.02	1.09	1.01	1.07	1.01	1.05	1.00	1.04	0.99	0.97			
10.0	1.24	1.07	1.23	1.07	1.22	1.07	1.16	1.05	1.16	1.05	1.15	1.05	1.10	1.03	1.09	1.03	1.09	1.03	1.00			

配光曲線



水平面照度

